



MEASUREMENTS SUBJECT TO A 3% VARIANCE.

CONSTRUCTION

- › METAL CONSTRUCTION WITH POLISHED CHROME FINISH
- › PLASTIC VALVE BODIES

MOUNTING

- › DESIGNED TO INSTALL THROUGH 3 HOLES, 7/8" (23mm) MIN. DIA. WITH 4" (102mm) CENTERS, ON DECKS UP TO 1" (25mm)
- › DESIGNED TO INSTALL MIN. 1-11/16" (43 mm) FROM VALVE CENTERLINE TO BACK SPLASH

INLET

- › 1/2"-14 NPSM THREADED MALE INLET SHANKS

OPERATION

- › QUARTER-TURN LEVER STYLE HANDLES
- › OPERATES WITH LESS THAN 5 LBS. OF FORCE

WATER-CONTROL MECHANISM

- › CERAMIC CARTRIDGE

FLOW

- › AERATOR LIMITS MAXIMUM FLOW RATE TO 1.5 GPM MAX.) @ 60 PSI

CODES/STANDARDS APPLICABLE

- › CSA
- › ASME A112.18.1/CSA B125.1
- › ANSI/NSF 372

GUARANTEE

- › LIMITED LIFETIME WARRANTY AGAINST DEFECTS IN MATERIAL AND WORK-MANSHIP TO ORIGINAL CONSUMER PURCHASER
- › 5 YEAR WARRANTY IF USED IN INDUSTRIAL, COMMERCIAL AND BUSINESS INSTALLATIONS

RETAIL PACK	POLISHED CHROME 26	CASE PACK
COLUMBIA TWO LEVER HANDLE LAVATORY FAUCET	06-4205P	6

